



**TERMOPLAST**



# TRP Product line



**INDUSTRIAL PARK**  
St. Aleea Plopilor no.1  
Roman, Romania



[www.termoplast.ro/en/home](http://www.termoplast.ro/en/home)




@termoplastromania





**TERMOPLAST**



# Sliding systems

Our agents can guide you towards the optimal solution for your project. **Contact us at +40 755 067 776!**



CHARACTERISTICS	SYNEGO SLIDE
Profile manufacturer	<b>REHAU</b>
Series type	Synego 80
Thermal coefficient Uf (w/m <sup>2</sup> K)	> 1.3
Frame depth (mm)	156
Number of frame seals	1
Maximum weight on sash(kg)	250
Maximum height (mm)	2500 white / 2300 coloured
Maximum frame length (mm)	4000 white welding or mechanical joining 3000 coloured welding; 4000 coloured(mechanical joining)
Maximum sash length (mm)	2000 white / 2000 coloured
Sash design	straight
Fixture (mm)	1.5 - 2.5
Base body colored	white
Seal colored on white body	grey
Standard colours*	plus 5-10 days**
Non-standard colours	plus 5-12 days**
Welding technology type	classic/invisible
Anthracite grey aluminium plating	—
Aluminium plating other colours	—
Soundproofing	up to 43
Glazing thickness (mm)	34 / 42 / 50
Sheets of glass	2/3
Burglary protection	up to RC2

\*Standard colours: walnut, anthracite grey, smooth anthracite grey, golden oak, weiss bianco, mooriche, black.

\*\*Number of days in addition to the standard delivery time.

CHARACTERISTICS	HST (LIFT & SLIDE)
Profile manufacturer	<b>REHAU</b>
Series type	Geneo
Thermal coefficient Uf (w/m <sup>2</sup> K)	1.3 - 1.8
Frame depth (mm)	203
Number of frame seals	2
Maximum weight on sash(kg)	400
Maximum height (mm)	2700 white / 2600 coloured
Maximum frame length (mm)	10000 white / 6800 coloured
Maximum sash length (mm)	3000 white / 2600 coloured
Sash design	straight
Fixture (mm)	1.5 - 2.5
Base body colored	white
Seal colored on white body	grey
Standard colours*	plus 5-10 days**
Non-standard colours	plus 5-12 days**
Welding technology type	classic/invisible
Anthracite grey aluminium plating	plus 3-5 days**
Aluminium plating other colours	plus 15-25 days
Soundproofing	40-45
Glazing thickness (mm)	24 / 36 / 44 / 52
Sheets of glass	2/3
Burglary protection	up to RC2

\*Standard colours: walnut, anthracite grey, smooth anthracite grey, golden oak, weiss bianco, mooriche, black.

\*\*Number of days in addition to the standard delivery time.

CHARACTERISTICS	SLIDING ON A PARALLEL PLANE
Profile manufacturer	SCHÜCO
Series type	All series
Thermal coefficient Uf (w/m <sup>2</sup> K)	0.84 - 1.3
Frame depth (mm)	70 / 80 / 82 / 86
Number of frame seals	2/3
Maximum weight on sash(kg)	200
Maximum height (mm)	2400 white/2200 coloured(70&Synego) 2700 white/2600 coloured(Geneo)
Maximum frame length (mm)	4000 white/ 3000 coloured
Maximum sash length (mm)	1600 white/1400 coloured(70&Synego) 2000 white/2000 coloured(Geneo)
Sash design	straight / rounded / faceted
Fixture (mm)	1.5 - 2.5
Base body colored	white
Seal colored on white body	white, grey, brown
Standard colours*	plus 2-5 days **
Non-standard colours	plus 5-12 days**
Welding technology type	classic/invisible
Anthracite grey aluminium plating	plus 2-5 days for Rehau**
Aluminium plating other colours	plus 15 - 25 days
Soundproofing	40-45
Glazing thickness (mm)	24 - 52
Sheets of glass	2/3
Burglary protection	up to RC3 (Rehau) / RC2 (Schüco)

\*Standard colours: walnut, anthracite grey, smooth anthracite grey, golden oak, weiss bianco, mooriche, black.

\*\*Number of days in addition to the standard delivery time.

CHARACTERISTICS	TILTABLE
Profile manufacturer	<b>REHAU</b>
Series type	Synego 80
Thermal coefficient Uf (w/m <sup>2</sup> K)	>1.1
Frame depth (mm)	80
Number of frame seals	2
Maximum weight on sash(kg)	50
Maximum height (mm)	2400 white / 2400 coloured
Maximum frame length (mm)	4000 white / 3000 coloured
Maximum sash length (mm)	4000 white / 3000 coloured
Sash design	straight
Fixture (mm)	2
Base body colored	white
Seal colored on white body	white, grey, brown
Standard colours*	plus 8 -15 days**
Non-standard colours	plus 8 -15 days**
Welding technology type	classic/invisible
Anthracite grey aluminium plating	—
Aluminium plating other colours	—
Soundproofing	46
Glazing thickness (mm)	50
Sheets of glass	2/3
Burglary protection	up to RC3

\*Standard colours: walnut, anthracite grey, smooth anthracite grey, golden oak, weiss bianco, mooriche, black.

\*\*Number of days in addition to the standard delivery time.

CHARACTERISTICS	SLINOVA
Profile manufacturer	<b>REHAU</b>
Series type	Slinova
Thermal coefficient Uf (w/m <sup>2</sup> K)	1.8
Frame depth (mm)	80, 146
Number of frame seals	2 brush seals
Maximum weight on sash(kg)	140
Maximum height (mm)	2600 white / 2450 coloured
Maximum frame length (mm)	4500 white / 4200 coloured
Maximum sash length (mm)	2000 white / 1500 coloured
Sash design	straight
Fixture (mm)	1.5 - 2.5
Base body colored	white
Seal colored on white body	grey
Standard colours*	plus 5-12 days**
Non-standard colours	plus 5-12 days**
Welding technology type	classic
Anthracite grey aluminium plating	—
Aluminium plating other colours	—
Soundproofing	33
Glazing thickness (mm)	24 / 32
Sheets of glass	2
Burglary protection	up to RC2

\*Standard colours: walnut, anthracite grey, smooth anthracite grey, golden oak, weiss bianco, mooriche, black.

\*\*Number of days in addition to the standard delivery time.



**TERMOPLAST**



# Window profiles

Our agents can guide you towards the optimal solution for your project. **Contact us at +40 755 067 776!**



## CHARACTERISTICS

## EURO 70

# REHAU®

Profile manufacturer	REHAU®
Profile materials	PVC
Profile thermal coefficient Uf (w/m <sup>2</sup> K)	1.3
Frame depth (mm)	70
Frame height (mm)	64 / 68
Number of sash rooms	5
Number of frame rooms	5
Number of frame seals	2
Window sash design	Straight/Rounded
Slim sash	–
Renovation frame on white body (mm)	40 / 60
Renovation frame on grey body (mm)	–
Renovation frame on brown body (mm)	–
Renovation frame on caramel body (mm)	–
Clip-on wing (mm)	40 / 60
Thermomodule / LowE Film	–
Fixture (mm)	1.5 / 2 / 2.5
PVC moulding type	Straight/Round
Base body colour	white / grey / brown
Gaskets colour on white body	grey
<b>COLOURS</b>	
White - anthracite grey / anthracite grey	on white body / grey body
White - anthracite grey glossy/anthracite grey glossy	on white body / brown body*
Walnut	on brown body
Golden Oak	on brown body
Weiss bianco	on white body
Mooreiche, black	on brown body
Non-standard colours on stock body	on white body / grey / brown*
Welding technology type	classic/invisible
Anthracite grey aluminium plating	–
Aluminium plating other colours	–
Schüco New Inside Hardware (concealed hinges)	–
Handles	Hoppe
Types of aluminium threshold (mm)	20
Extensions (mm)* <b>and multiples</b>	20 / 40 / 60
Mounting height (mm)	30
Arched frames	plus 5 - 8 days*
Soundproofing	up to 45 dB
Glazing thickness (mm)	24 / 32 / 40
Sheets of glass	2/3
Burglary protection	up to RC3

\*Delivery times 3-12 days more than standard

\*\*Details at TRP consultants

## CHARACTERISTICS

## CORONA CT70

# SCHÜCO

Profile manufacturer	SCHÜCO
Profile materials	PVC
Profile thermal coefficient Uf (w/m <sup>2</sup> K)	1.3
Frame depth (mm)	70
Frame height (mm)	68
Number of sash rooms	5
Number of frame rooms	5
Number of frame seals	2
Window sash design	Straight/Rounded
Slim sash	Da
Renovation frame on white body (mm)	30 / 58
Renovation frame on grey body (mm)	30 / 58
Renovation frame on brown body (mm)	–
Renovation frame on caramel body (mm)	30 / 58
Clip-on wing (mm)	50
Thermomodule / LowE Film	–
Fixture (mm)	1.5 / 2
PVC moulding type	Straight/Round
Base body colour	white / grey / caramel
Gaskets colour on white body	grey
<b>COLOURS</b>	
White - anthracite grey / anthracite grey	on white body / grey body *
White - anthracite grey glossy/anthracite grey glossy	on white body / grey body
Walnut	on grey body
Golden Oak	on caramel body
Weiss bianco	on white body
Mooreiche, black	on grey body*
Non-standard colours on stock body	on white body / grey / caramel*
Welding technology type	classic/invisible/HFL
Anthracite grey aluminium plating	–
Aluminium plating other colours	–
Schüco New Inside Hardware (concealed hinges)	Yes
Handles	Schüco, Hoppe
Types of aluminium threshold (mm)	20
Extensions (mm)* <b>and multiples</b>	25 / 50 / 60
Mounting height (mm)	30
Arched frames	plus 5 - 8 days*
Soundproofing	up to 46 dB
Glazing thickness (mm)	24 / 28 / 40
Sheets of glass	2/3
Burglary protection	up to RC2

\*Delivery times 3-12 days more than standard

\*\*Details at TRP consultants

# CHARACTERISTICS

# SYNEGO 80

## REHAU®

Profile manufacturer	REHAU®
Profile materials	PVC
Profile thermal coefficient Uf (w/m <sup>2</sup> K)	1.0
Frame depth (mm)	80
Frame height (mm)	72
Number of sash rooms	6
Number of frame rooms	7
Number of frame seals	3
Window sash design	Straight
Slim sash	–
Renovation frame on white body (mm)	40
Renovation frame on grey body (mm)	40
Renovation frame on brown body (mm)	40
Renovation frame on caramel body (mm)	–
Clip-on wing (mm)	40 / 60
Thermomodule / LowE Film	–
Fixture (mm)	1.5 / 2 / 2.5
PVC moulding type	Straight/Round
Base body colour	white / grey / brown
Gaskets colour on white body	grey
<b>COLOURS</b>	
White - anthracite grey / anthracite grey	on white body / grey body
White - anthracite grey glossy/anthracite grey glossy	on white body / brown body*
Walnut	on brown body
Golden Oak	on brown body
Weiss bianco	on white body*
Mooreiche, black	on brown body
Non-standard colours on stock body	on white body / grey / brown*
Welding technology type	classic/invisible
Anthracite grey aluminium plating	plus 3 - 5 days**
Aluminium plating other colours	plus 15 - 25 days
Schüco New Inside Hardware (concealed hinges)	–
Handles	Hoppe
Types of aluminium threshold (mm)	20
Extensions (mm)* <b>and multiples</b>	20 / 45 / 60 / 100
Mounting height (mm)	30
Arched frames	plus 5 - 8 days*
Soundproofing	up to 46 dB
Glazing thickness (mm)	34 / 42 / 50
Sheets of glass	2/3
Burglary protection	up to RC3

\*Delivery times 3-12 days more than standard

\*\*Details at TRP consultants



## CHARACTERISTICS

## LIVING 82

# SCHÜCO

Profile manufacturer	SCHÜCO
Profile materials	PVC
Profile thermal coefficient Uf (w/m <sup>2</sup> K)	>0.96
Frame depth (mm)	82
Frame height (mm)	70
Number of sash rooms	7
Number of frame rooms	7
Number of frame seals	3
Window sash design	Straight
Slim sash	–
Renovation frame on white body (mm)	50
Renovation frame on grey body (mm)	50
Renovation frame on brown body (mm)	–
Renovation frame on caramel body (mm)	–
Clip-on wing (mm)	50
Thermomodule / LowE Film	–
Fixture (mm)	1.5 / 2
PVC moulding type	Straight
Base body colour	white / grey
Gaskets colour on white body	grey, black
<b>COLOURS</b>	
White - anthracite grey / anthracite grey	on white body / grey body*
White - anthracite grey glossy/anthracite grey glossy	on white body / grey body
Walnut	on grey body
Golden Oak	on grey body
Weiss bianco	on white body
Mooreiche, black	on grey body*
Non-standard colours on stock body	on white body / grey*
Welding technology type	classic/invisible
Anthracite grey aluminium plating	–
Aluminium plating other colours	–
Schüco New Inside Hardware (concealed hinges)	Yes
Handles	Schüco, Hoppe
Types of aluminium threshold (mm)	20
Extensions (mm)* <b>and multiples</b>	30 / 50
Mounting height (mm)	Schüco 60 with seal and barrier
Arched frames	plus 15 - 25 days*
Soundproofing	up to 47 dB
Glazing thickness (mm)	28 / 44 / 52
Sheets of glass	2/3
Burglary protection	up to RC2

\*Delivery times 3-12 days more than standard

\*\*Details at TRP consultants

## CHARACTERISTICS

## GENEO 86

# REHAU®

Profile manufacturer	RAU FIPRO
Profile materials	RAU FIPRO
Profile thermal coefficient Uf (w/m <sup>2</sup> K)	>0.79
Frame depth (mm)	86
Frame height (mm)	72 / 86
Number of sash rooms	6
Number of frame rooms	6
Number of frame seals	3
Window sash design	Straight
Slim sash	–
Renovation frame on white body (mm)	–
Renovation frame on grey body (mm)	–
Renovation frame on brown body (mm)	–
Renovation frame on caramel body (mm)	–
Clip-on wing (mm)	40 / 60
Thermomodule / LowE Film	Da
Fixture (mm)	1.5 / 2 / 2.5
PVC moulding type	Straight
Base body colour	white / (grey, brown, caramel)**
Gaskets colour on white body	grey
<b>COLOURS</b>	
White - anthracite grey / anthracite grey	on white body / grey body *
White - anthracite grey glossy/anthracite grey glossy	on white body*
Walnut	on brown body*
Golden Oak	on caramel body*
Weiss bianco	on white body*
Mooreiche, black	on brown body*
Non-standard colours on stock body	on white body*
Welding technology type	classic/invisible
Anthracite grey aluminium plating	–
Aluminium plating other colours	–
Schüco New Inside Hardware (concealed hinges)	–
Handles	Hoppe
Types of aluminium threshold (mm)	20
Extensions (mm)* <b>and multiples</b>	20 / 40 / 60
Mounting height (mm)	30
Arched frames	plus 5 - 8 days*
Soundproofing	up to 47 dB
Glazing thickness (mm)	44 / 52
Sheets of glass	3
Burglary protection	up to RC3

\*Delivery times 3-12 days more than standard

\*\*Details at TRP consultants

## CHARACTERISTICS

## ARTEVO

# REHAU®

Profile manufacturer	RAU FIPRO
Profile materials	RAU FIPRO
Profile thermal coefficient Uf (w/m <sup>2</sup> K)	>0.60
Frame depth (mm)	80
Frame height (mm)	65
Number of sash rooms	5-8
Number of frame rooms	7
Number of frame seals	3
Window sash design	Straight/Coplanar
Slim sash	—
Renovation frame on white body (mm)	—
Renovation frame on grey body (mm)	—
Renovation frame on brown body (mm)	—
Renovation frame on caramel body (mm)	—
Clip-on wing (mm)	40 / 60
Thermomodule / LowE Film	LowE Film
Fixture (mm)	1.5 / 2 / 2.5
PVC moulding type	Straight
Base body colour	white / (brown)**
Gaskets colour on white body	grey
<b>COLOURS</b>	
White - anthracite grey / anthracite grey	on white body / brown body *
White - anthracite grey glossy/anthracite grey glossy	on white body*
Walnut	on brown body*
Golden Oak	on brown body*
Weiss bianco	on white body*
Mooreiche, black	on brown body*
Non-standard colours on stock body	on white body*
Welding technology type	classic/invisible
Anthracite grey aluminium plating	—
Aluminium plating other colours	—
Schüco New Inside Hardware (concealed hinges)	—
Handles	Hoppe
Types of aluminium threshold (mm)	20
Extensions (mm)* <b>and multiples</b>	20 / 45 / 60 / 100
Mounting height (mm)	30
Arched frames	plus 5 - 8 days*
Soundproofing	up to 48 dB
Glazing thickness (mm)	34 / 56
Sheets of glass	2/3
Burglary protection	up to RC3

\*Delivery times 3-12 days more than standard

\*\*Details at TRP consultants